

HCH-CN50-DC

DC Travel Charger for Intermecc® CN50 Mobile Computer

Charger Specifications:

Input Voltage: 10V - 32V DC
Input Current: 1Amp Max
Output Voltage: 4.65V DC
Output Current: 1.5Amp Max
Operating Temp: 0°C - 40°C
(32°F - 104°F)
Storage Temp: -10°C - 50°C
(15°F - 125°F)
Charging Time: Determined by Device

Dimensions:

Width: 3.1 inches (80 mm)
Length: 2 inches (51 mm)
Height: 3.4 inches (87 mm)
Excluding Power Cord
Power Cord Length: 2 feet
Weight: 242 g (Including Power Cord)

Warranty:

Each charger is guaranteed to be free from defects in materials and workmanship for 12 months from date of shipment under normal use.



Trademarks are the sole property of their respective owners.
The Honeywell® Trademark is used under license from Honeywell® International Inc.

11.07.18



Features :

- Light weight, versatile and portable design for in-vehicle use.
- Includes power supplies and cable.
- Compatible with RAM Mount.
- Cup has reinforced pins to avoid easy breakage.
- Connectors and cigarette lighter plug have been improved to industrial grade and reinforced from original design.

For Pricing or Additional Information Contact:

Global Technology Systems, Inc.
550 Cochituate Road Framingham, MA 01701
800.267.2711 ■ In Europe call: 00800.5390.5390
www.GTSpower.com